

ANT27S, ANT27M, ANT27L

27MHz 50 Ohms Antenna

Features

- 3 versions – ANT27S (40cm), ANT27M (100 cm) and ANT27L (180cm)
- Ground Plain required (only for ANT27S). ANT27M and ANT27L is ground Independent
- Unbreakable Mount
- Removable Whip unscrews from Mount
- Mounting Socket Required –SO239 (Only for ANT27S)
- Supplied with 3.60 metre cable and connector (ANT27M and ANT27L)
- Pre-tuned to 27.145MHz



Application




- For use with Elsema 27MHz transmitters and receivers.

Description

The ANT27S requires a SO239 socket and screws directly onto the socket.

The ANT27M and ANT27L comes with a 3.6metre cable and PL259 connector. The ANT27M is a 1.0meter long while the Ant27L is 1.8meters long Helical whip with Ground Independent Mounting.

Products in Range

		
ANT27S	ANT27M	ANT27L

Specifications

	ANT27S	ANT27M	ANT27L
Type	Ground Dependent Helical Whip	Ground Independent Helical Whip	Ground Independent Helical Whip
Length	40cm	1.0m	1.8cm
Cable Length	-	3.6m	3.6m
Frequency	27.145MHz	27.145MHz	27.145MHz
Tuning	Factory Preset	Factory Preset	Factory Preset
V.S.W.R	Less than 1.5:1	Less than 1.5:1	Less than 1.5:1
Impedance	50Ω Nominal	50Ω Nominal	50Ω Nominal
Max Power	25W	20W	20W
Termination	SMA Connection		SMA Connection
Mounting	Bottom Terminated	Pre-terminated feedline with PL259	Pre-terminated feedline with PL259
Pattern	Omni Directional	Omni Directional	Omni Directional

Manufactured by

Elsema Pty Ltd
3/10 Hume Rd, Smithfield
NSW 2164
Ph: 02 9609 4668
Fax: 02 9725 2663
Website: <http://www.elsema.com>